



DIESEL TURBO VHPD 5W30

DIESEL

Description

Synthetic lubricating oil for heavy vehicles with very high performance. It meets the requirements of most manufacturers for being considered Long Life. Furthermore, it is characterised by its viscosity and ability to work at any temperature, save fuel and contribute to reducing CO₂ emissions to the atmosphere. It is compatible with EGR systems (Exhaust Gas Recirculation) and SCR catalytic converters, and can be used by biodiesel engines. It is a very modern lubricant that complies with Euro 5 standards on polluting emissions.

Properties

- Long-life lubricating oil that makes it possible to reduce maintenance costs and waste generation.
- It can be used when using biodiesel as fuel, in accordance with the manufacturer-recommended change periods.
- Results show fuel savings of approximately 200 litres/year compared to other 5W30 oils on the market (*)
- Suitable for vehicles undertaking international long-hauls by road; it also has a long change period, as its high alkaline reserve allows it to be used with fuels of varying quality.

(*) Data obtained with an average estimate of a truck that travels 150,000 km/year.

Quality level

- ACEA E7/E4
- VOLVO VDS-3
- DEUTZ DQC III-10
- MAN 3277
- MTU Type 3
- MACK EO-N
- MB 228.5
- Renault VI RXD, RLD-2
- DAF Extended Drain

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			5W30
Density at 15°C	g/cm ³	ASTM D 4052	0.858
Viscosity at 100°C	cSt	ASTM D 445	12.25
Viscosity at 40°C	cSt	ASTM D 445	75
Viscosity at -30°C	cP	ASTM D 5293	6600 max
Viscosity rate	-	ASTM D 2270	163
Flash point, open cup	°C	ASTM D 92	225 min.
Pour point	°C	ASTM D 97	-39 max
T. B. N.	mg KOH/g	ASTM D 2896	15.5
Bosch Injector Shearing: Viscosity at 100°C after shear	cSt	CEC-L-14-93	9.3 min.
Sulphated ashes	% in weight	ASTM D 874	1.8

■ Hazard identification

This product is not classified as toxic or hazardous under current legislation.

■ Handling

Avoid prolonged contact and prolonged inhalation of product vapours or spray.
The use of gloves, visors or glasses is recommended to avoid danger from splashes.

■ Health and safety hazards

Inhalation: In case of inhaling, move outdoors. Seek medical advice

Ingestion: Do not induce vomiting. Give water. Seek medical advice

Contact with Skin/Eyes: Wash thoroughly with soap and water. Seek medical advice

General measures: Seek medical advice

■ Fire-fighting measures

No special measures required.

Fire-extinguishing measures: Foams, dry chemicals, CO₂, water spray. Do not directly apply the jet of water, as this could cause the product to spread.

■ Environmental precautions

Danger of physical pollution if spilt (water, coastlines, soil, etc.) due to its floatability and oily consistency that may harm flora and fauna on contact. Prevent the material from entering water outlets.

Decontamination and cleaning: Treat as an accidental oil spill. Prevent spreading by using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

repsolypf.com

Unless otherwise indicated, the figures cited in the technical specifications should be considered typical